

Product Technical Data Sheet PRODUCENT: AG Termopasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły, tel. 86 274 13 42

KONTAKT U

The formulation is a composition of solvents that allows cleaning and degreasing of electrical components and contacts. Kontakt U is an agent that effectively removes residual grease, dirt; old lubricants, oils, silicones, sulphides and oxides dissolved with Kontakt S as well as any soldering residues (including rosin). The formulation protects against corrosion and ensures low contact transition resistance.

Application:

- degreasing of components and contacts
- cleaning of components and contacts
- good lubricating properties

Physicochemical properties of the liquid:

Parameters	UoM	Result
Relative density at 20°C	g/cm³	0,74
Viscosity	MPa∙s	18,6

Packagings:

Volume	Collective packaging	Item Code
60 ml (aerosol)	4 or 20	ART.AGT-011
300 ml (aerosol)	4 or 20	ART.AGT-012
400 ml (aerosol with a brush)	4 or 20	ART.AGT-226
1000 ml (bottle)	4 or 20	ART.AGT-097

Warehousing

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect against electrostatic discharge.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.

