

Product Technical Data Sheet PRODUCENT: AG Termopasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły, tel. 86 274 13 42

Printer

A printing mechanism cleaning agent for printers (paper feeding mechanisms, printhead drive components etc.), cleans heads in needle printers, the preparation does not react with plastics used in printers.

Application:

- printers
- computers

Physicochemical properties:

| Parameters | UoM | Result |
|------------|-------------------|--------------------|
| Appearance | - | transparent liquid |
| Density | g/cm ³ | 0.700 |
| Odour | - | alcohol |

Packagings:

| Volume | Collective packaging | Item Code |
|------------------|----------------------|-------------|
| 400 ml (aerosol) | 4 or 24 | ART.AGT-185 |

Warehousing:

Keep in a well-ventilated place, in accordance with the applicable fire protection and safety regulations - a fire-proofed storage, without heating, explosion-proof electrical and ventilation system, flooring with electro-conductive lining; metal devices and storage facilities, tanks, containers, packages etc., where electrical charges can accumulate should be grounded. Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from children.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.

